NSN 5930-00-525-1806

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-525-1806

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.200 inches
Body Width:
0.281 inches
Body Height:
0.825 inches
Unthreaded Mounting Hole Diameter:
Between 0.093 inches and 0.096 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.625 inches
Actuator Style:
Round
Actuator Free Position Height:
0.234 inches
Maximum Voltage Rating In Volts:
125.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
Between 3.0 ounces and 5.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.031 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

NSN 5930-00-525-1806

Sensitive Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0