NSN 5930-00-525-5473

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-525-5473

view Offilite at https://aerobasegroup.com/hist//3330-00-323-3473
Body Style:
Panel mounted
Overall Length:
2.720 inches
Overall Height:
0.800 inches
Overall Width:
0.800 inches
Body Width:
0.800 inches
Body Height:
0.800 inches
Actuator Length:
0.684 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.684 inches
Actuator Color:
Yellow single actuator and red single actuator
Illuminated Actuator Color:
Yellow 1st actuator
Illuminated Actuator Color Sequence:
Top half of actuator yellow bottom half of actuator red
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.720 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000
amperes inductive ac and 750.000 milliamperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

17 tab solder lug

NSN 5930-00-525-5473

Push Switch - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-s-22885/56 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0