# NSN 5930-00-525-5482

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-525-5482

- **Body Style:**
- Panel mounted
- **Overall Length:**
- 2.720 inches
- **Overall Height:**
- 0.800 inches
- **Overall Width:**
- 0.800 inches
- Body Width:
- 0.800 inches
- **Body Height:**
- 0.800 inches
- Actuator Length:
- 0.684 inches
- Actuator Style:

## Rectangular

- Actuator Height:
- 0.070 inches
- Actuator Width:
- 0.684 inches
- Actuator Color:
- Red single actuator
- Illuminated Actuator Color:
- Red single actuator
- Maximum Voltage Rating In Volts:
- 115.0 ac and 28.0 dc
- Mounting Surface To Terminal End Distance:
- 2.650 inches
- Inclosure Type:
- Fully enclosed
- **Mounting Method:**

Panel

- Nonpile-up Contact Arrangement:
- 2 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

#### Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

11 tab, solder lug

Specification Data:

# NSN 5930-00-525-5482

Push Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

