

View Online at <https://aerobasegroup.com/nsn/5930-00-525-5608>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

1.640 inches

Body Width:

1.320 inches

Body Height:

1.100 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.050 inches

Actuator Position-action Relationship:

Up position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and center position locked out

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

F-14a

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 12.000 amperes inductive dc and 5.000 amperes lamp dc and 8.000 amperes resistive ac and 6.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0