NSN 5930-00-528-1648

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-528-1648

Thread Class: 3a single pressure connection **Overall Length:** 2.600 inches **Outside Diameter:** 0.438 inches single connection **Body Length:** 1.550 inches **Overall Diameter:** 0.680 inches **Pressure Switch Type:** Absolute **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit **Mounting Method:** Clamp **Contact Action Stimulus:** Increase **Proof Pressure:** 270.00 kilograms per square centimeter **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Sensing Element Burst Pressure:** 450.00 pounds per square inch absolute **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 1.0 amperes inductive load single voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 37.50 actuation point pounds per square inch absolute and 32.50 deactuation point pounds per square inch absolute **Contact Voltage Rating In Volts:** 28.0 dc at sea level single voltage **Pressure Connector Type:** Flared, threaded external single connection Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

NSN 5930-00-528-1648

Pressure Switch - Page 2 of 2



Thread	Series	Design	ator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0