

View Online at <https://aerobasegroup.com/nsn/5930-00-528-1648>

Thread Class:

3a single pressure connection

Overall Length:

2.600 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.550 inches

Overall Diameter:

0.680 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Clamp

Contact Action Stimulus:

Increase

Proof Pressure:

270.00 kilograms per square centimeter

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

450.00 pounds per square inch absolute

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

37.50 actuation point pounds per square inch absolute and 32.50 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0