NSN 5930-00-528-9544



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-528-9544 **Body Style:** Panel mounted **Overall Length:** 2.750 inches **Overall Height:** 0.688 inches **Overall Width:** 0.688 inches **Body Width:** 0.688 inches **Body Height:** 0.688 inches **Case Material:** Metal **Actuator Length:** 0.530 inches **Actuator Style:** Rectangular **Actuator Height:** 0.070 inches **Actuator Width:** 0.530 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** Green and amber single actuator **Actuator Inscription:** Sono cmd single actuator **Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.620 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

NSN 5930-00-528-9544

Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0