## NSN 5930-00-528-9554

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-528-9554

| Body Style:   |
|---|
| Panel mounted   |
| Overall Length:   |
| 0.688 inches  |
| Overall Height:   |
| 0.688 inches  |
| Overall Width:  |
| 0.688 inches  |
| Body Width:   |
| 0.688 inches  |
| Body Height:  |
| 0.688 inches  |
| Actuator Length:  |
| 0.620 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.070 inches  |
| Actuator Width:   |
| 0.620 inches  |
| Actuator Color:   |
| Green and amber single actuator   |
| Illuminated Actuator Color:   |
| Green and amber single actuator   |
| Actuator Inscription:   |
| Hf 0n single actuator   |
| Maximum Voltage Rating In Volts:  |
| 230.0 ac and 28.0 dc  |
| Mounting Surface To Terminal End Distance:  |
| 2.750 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Features Provided:  |
| Rfi shielding   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary single switch unit   |
| Contact Load Current Rating At Maximum Rated Voltage:   |
| 7 000 amneres resistive dc and 4 000 amneres inductive dc and 7 000 amneres resistive ac and 4 000 amneres inductive ac |

Contacts silver

**Precious Material And Location:** 

## NSN 5930-00-528-9554

Push Switch - Page 2 of 2



| Terminal Type And Quantity | /: |
|----------------------------|----|
|----------------------------|----|

3 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0