# NSN 5930-00-528-9568

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-528-9568

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof

# **Overall Length:**

2.750 inches

#### **Overall Height:**

0.688 inches

#### **Overall Width:**

0.688 inches

#### **Body Width:**

0.688 inches

#### **Body Height:**

0.688 inches

#### Case Material:

Metal

# Actuator Length:

0.620 inches

Actuator Style:

# Rectangular

# Actuator Height:

0.070 inches

### Actuator Width:

0.620 inches

#### Actuator Color:

Green and amber and green and amber single actuator

#### **Illuminated Actuator Color:**

Green and amber and green and amber single actuator

#### **Actuator Inscription:**

Usb I5b single actuator

#### Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

2.680 inches

#### Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

#### **Features Provided:**

Rfi shielding

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

# NSN 5930-00-528-9568

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

#### Precious Material And Location:

Contacts silver

# Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

### Fiig:

A053a0