

View Online at <https://aerobasegroup.com/nsn/5930-00-529-5941>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

1.000 inches

Bushing Length:

0.812 inches

Body Length:

2.907 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.781 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.120 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thread Size:

1.000 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

72.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0