NSN 5930-00-530-4635

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-530-4635

| Body Style: |
|---|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Explosion proof |
| Overall Length: |
| 0.750 inches |
| Overall Height: |
| 2.770 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 0.688 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 2.530 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.150 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| Green and amber and green and amber single actuator |
| Illuminated Actuator Color: |
| Green and amber and green and amber single actuator |
| Actuator Inscription: |
| Uhf-1 xmit single actuator |
| Maximum Voltage Rating In Volts: |
| 230.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |

Nonpile-up Contact Arrangement:

Rfi shielding

Nonplie up Contact Arrangement.

1 pole, double throw, both positions maintained single switch unit

NSN 5930-00-530-4635

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Precious Material And Location:

Terminal surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0