

View Online at <https://aerobasegroup.com/nsn/5930-00-530-4635>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

0.750 inches

**Overall Height:**

2.770 inches

**Overall Width:**

0.750 inches

**Body Length:**

0.688 inches

**Body Width:**

0.750 inches

**Body Height:**

2.530 inches

**Case Material:**

Metal

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.150 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

Green and amber and green and amber single actuator

**Illuminated Actuator Color:**

Green and amber and green and amber single actuator

**Actuator Inscription:**

Uhf-1 xmit single actuator

**Maximum Voltage Rating In Volts:**

230.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

**Precious Material And Location:**

Terminal surfaces gold and contacts silver

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Type And Quantity:**

3 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0