NSN 5930-00-530-4645

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-530-4645

view Offilite at https://defobasegroup.com/histi/05500-00-5500-4045
Body Style:
Panel mounted
Overall Length:
2.770 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.530 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.530 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green and amber single actuator
Actuator Inscription:
Alt ics single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.620 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
3 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

NSN 5930-00-530-4645Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
9 turret and 5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0