## NSN 5930-00-530-4648



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-530-4648 **Body Style:** Panel mounted **Overall Length:** 2.770 inches **Overall Height:** 0.750 inches **Overall Width:** 0.750 inches **Body Width:** 0.750 inches **Body Height:** 0.750 inches **Case Material:** Metal **Actuator Length:** 0.530 inches **Actuator Style:** Rectangular **Actuator Height:** 0.090 inches **Actuator Width:** 0.530 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** Green and amber single actuator **Actuator Inscription:** Ics disc single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Mounting Surface To Terminal End Distance:** 2.620 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Panel

**Features Provided:** 

Rfi shielding

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary single switch unit

## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

## NSN 5930-00-530-4648

Push Switch - Page 2 of 2



Pracious	Material	And	Location:
Precious	wateriai	Ana	Location:

Contacts silver

**Terminal Type And Quantity:** 

3 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0