NSN 5930-00-530-4649



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-530-4649 **Body Style:** Panel mounted **Overall Length:** 2.770 inches **Overall Height:** 0.750 inches **Overall Width:** 0.750 inches **Body Width:** 0.750 inches **Body Height:** 0.750 inches **Case Material:** Metal **Actuator Length:** 0.530 inches **Actuator Style:** Rectangular **Actuator Height:** 0.090 inches **Actuator Width:** 0.530 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** Green and amber single actuator **Actuator Inscription:** Over ride single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Mounting Surface To Terminal End Distance:** 2.620 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

NSN 5930-00-530-4649Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
9 turret and 5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0