

View Online at <https://aerobasegroup.com/nsn/5930-00-530-4922>

**Body Style:**

Bushing mounted

**Body Length:**

0.400 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.070 inches

**Actuator Height:**

0.040 inches

**Actuator Free Position Height:**

0.040 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.439 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

30.0 ounces

**Actuator Movement:**

Between 0.007 pretravel inches and 0.003 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 7.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

32 in. Lg wire leads

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0