

View Online at <https://aerobasegroup.com/nsn/5930-00-530-4922>

Body Style:

Bushing mounted

Body Length:

0.400 inches

Actuator Style:

Round

Actuator Diameter:

0.070 inches

Actuator Height:

0.040 inches

Actuator Free Position Height:

0.040 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.439 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

30.0 ounces

Actuator Movement:

Between 0.007 pretravel inches and 0.003 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 7.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

32 in. Lg wire leads

Thread Series Designator:

Un

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0