

View Online at <https://aerobasegroup.com/nsn/5930-00-531-9194>

Body Style:

Panel mounted

Overall Length:

3.250 inches

Overall Height:

1.200 inches

Overall Width:

0.960 inches

Body Width:

0.960 inches

Body Height:

1.200 inches

Case Material:

Metal

Actuator Length:

1.040 inches

Actuator Style:

Rectangular

Actuator Height:

0.140 inches

Actuator Width:

0.800 inches

Actuator Color:

Green single actuator and amber single actuator

Illuminated Actuator Color:

Green single actuator and amber single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

3.110 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-prf-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 tab solder lug and 12 turret

Specification Data:

81349-mil-prf-22885/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-prf-22885 spec.