NSN 5930-00-531-9360

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-531-9360

Thread Class:
2a single mounting facility
Thread Length:
0.469 inches single mounting facility
Hazardous Locations/environmental Protection
Explosion proof
Overall Length:
5.688 inches
Overall Diameter:
2.000 inches
Individual Section Quantity:
7
Knob Manufacturer Code:
82121
Nonturn Device Type:
Slotted bushing at 12: 00 o'clock
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
7 each section front
Mounting Method:
Threaded bushing single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.469 inches single mounting facility
Contact Voltage Rating In Volts:
125.0 ac at sea level
Switch Actuator Indexing Position Quantity:
8 single actuator
Criticality Code Justification:
Feat
Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks 4th section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator

NSN 5930-00-531-9360

Rotary Switch - Page 2 of 2



Contact Load Current Ratin

5.0 amperes resistive load ac at sea level

Special Features:

Item must comply with rqmt of desc production standard no. L01645

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0