NSN 5930-00-532-0992

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-532-0992

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.770 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.150 inches

Actuator Width:

0.620 inches

Actuator Color:

Green and amber single actuator

Illuminated Actuator Color:

Green and amber single actuator

Actuator Inscription:

Auto single actuator

Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.620 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-00-532-0992

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0