NSN 5930-00-532-1240

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-532-1240

Overall Length:
1.250 inches
Overall Height:
0.440 inches
Overall Width:
0.401 inches
Body Length:
0.776 inches
Body Width:
0.401 inches
Body Height:
0.251 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
1.000 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -80.0 degrees fahrenheit and 300.0 degrees fahrenheit
Mounting Method:
Mounting Method: Bracket and unthreaded hole
_
Bracket and unthreaded hole
Bracket and unthreaded hole Features Provided:
Bracket and unthreaded hole Features Provided: Hermetically sealed case
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus:
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern:
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement:
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type:
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 2.5 amperes resistive load first voltage
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 2.5 amperes resistive load first voltage Contact Adjustability:
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 2.5 amperes resistive load first voltage Contact Adjustability: Actuation point adjustable, preset
Bracket and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 2.5 amperes resistive load first voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range:

Contact Stimulus Rating:

125.00 actuation point degrees fahrenheit

NSN 5930-00-532-1240

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0