

View Online at <https://aerobasegroup.com/nsn/5930-00-532-8012>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

5.875 inches

**Overall Height:**

3.312 inches

**Overall Width:**

3.375 inches

**Body Height:**

3.125 inches

**Unthreaded Mounting Hole Diameter:**

0.219 inches

**Capillary Tube Length:**

84.0 inches

**Bulb Length:**

11.250 inches

**Bulb Diameter:**

0.188 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.438 inches

**Longest Vertical Distance Between Mounting Centers:**

3.875 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Flush and unthreaded hole

**Features Provided:**

Calibrated scale

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

4.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+50.00/+250.00 actuation point degrees fahrenheit and +50.00/+250.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point knob with scale and external actuation point knob with scale

**Contact Voltage Rating In Volts:**

277.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0