

View Online at <https://aerobasegroup.com/nsn/5930-00-532-8012>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.875 inches

Overall Height:

3.312 inches

Overall Width:

3.375 inches

Body Height:

3.125 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Capillary Tube Length:

84.0 inches

Bulb Length:

11.250 inches

Bulb Diameter:

0.188 inches

Longest Horizontal Distance Between Mounting Centers:

2.438 inches

Longest Vertical Distance Between Mounting Centers:

3.875 inches

Tempurature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Flush and unthreaded hole

Features Provided:

Calibrated scale

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

4.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+250.00 actuation point degrees fahrenheit and +50.00/+250.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

277.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0