NSN 5930-00-534-6346

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-534-6346

Body Style:	
Panel mounted	
Hazardous Locations/environmental Protection:	
Explosion proof	
Overall Length:	
2.750 inches	
Overall Height:	
0.688 inches	
Overall Width:	
0.688 inches	
Body Width:	
0.688 inches	
Body Height:	
0.688 inches	
Case Material:	
Metal	
Actuator Length:	
0.620 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.070 inches	
Actuator Width:	
0.620 inches	
Actuator Color:	
Green and amber single actuator	
Illuminated Actuator Color:	
Green and amber single actuator	
Actuator Inscription:	
Uhf on single actuator	
Maximum Voltage Rating In Volts:	
230.0 ac and 28.0 dc	
Mounting Surface To Terminal End Distance:	
2.620 inches	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel	
Features Provided:	
Rfi shielding	
Nonpile-up Contact Arrangement:	
1 pole, double throw, one position momentary single switch unit	

NSN 5930-00-534-6346

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0