# NSN 5930-00-535-4138

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-535-4138

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

4.000 inches

### **Overall Height:**

1.312 inches

#### **Overall Width:**

1.250 inches

#### First Flat Length:

0.750 inches single actuator

### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

2.125 inches single actuator

## Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

### Pole Quantity:

2 each section rear

### **Throw Quantity:**

2 each section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

2 single actuator

### Shaft Type:

Round, flatted single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-535-4138

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

#### Precious Material And Location:

Contact clips and rotors silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0