# NSN 5930-00-535-4146

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-535-4146

### **Thread Length:**

0.250 inches single mounting facility

## **Overall Length:**

3.562 inches

## **Overall Height:**

1.312 inches

## **Overall Width:**

1.250 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.562 inches single actuator

# Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

# Individual Section Quantity:

4

Nonturn Device Type:

Tab at 3: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### **Throw Quantity:**

7 each section rear

#### Mounting Method:

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

7 single actuator

#### Shaft Type:

Round, v flatted single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-535-4146

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 30.0 degrees single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0