## NSN 5930-00-537-7006

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-537-7006

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.035 inches **Overall Height:** 1.437 inches **Overall Width:** 1.312 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.380 inches single actuator **Nonturn Device Radius:** 0.437 inches at 9: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section front **Throw Quantity:** 5 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-537-7006

Rotary Switch - Page 2 of 2



## **Switch Actuator Stop Device Type:**

Adjustable stop single actuator

## **Contact Load Current Rating:**

1.5 amperes resistive load dc at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0