

View Online at <https://aerobasegroup.com/nsn/5930-00-538-0404>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

3.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches

Overall Height:

0.938 inches

Overall Width:

1.750 inches

Body Length:

2.250 inches

Body Width:

0.906 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.219 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.344 inches

Actuator Length:

1.250 inches

Actuator Style:

Leaf

Actuator Width:

0.500 inches

Actuator Free Position Height:

0.625 inches

Maximum Voltage Rating In Volts:

24.0 dc

End Application:

Sealift support facilities program (ssfp) equipment

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.015 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 7.500 amperes inductive dc and 7.500 amperes lamp dc

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0