## NSN 5930-00-538-1332

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-538-1332

Body Style:
Hole mounted
Overall Length:
2.000 inches
Overall Width:
1.032 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.500 inches
Housing Height:
1.125 inches
Housing Length:
2.000 inches
Housing Width:
1.032 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.437 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.375 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
64.0 ounces
Switch Actuating Force:
80.0 ounces
Actuator Movement:
0.100 pretravel inches and 0.125 overtravel inches and 0.025 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 10.000 amperes resistive ac

Shelf Life: N/a

**Terminal Type And Quantity:** 

4 connector, receptacle

## NSN 5930-00-538-1332

Sensitive Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0