## NSN 5930-00-538-2891

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-538-2891

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.930 inches
Body Width:
0.688 inches
Body Height:
1.130 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.170 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.156 inches
Maximum Voltage Rating In Volts:
230.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
4.0 ounces
Actuator Movement:
Between 0.093 pretravel inches and 0.031 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
0.500 amperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a

## NSN 5930-00-538-2891

Sensitive Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0