NSN 5930-00-538-2973

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-538-2973

Overall Length:
7.750 inches
Overall Height:
6.375 inches
Overall Width:
5.500 inches
Distance Between Mounting Facility Centers:
8.900 inches
Capillary Tube Length:
84.000 inches
Bulb Length:
5.500 inches
Bulb Diameter:
0.250 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
Between -273.1 degrees celsius and 50.0 degrees fahrenheit
Mounting Method:
Mounting Method: Base
-
Base
Base Features Provided:
Base Features Provided: Tubing end seal connection
Base Features Provided: Tubing end seal connection Contact Action Stimulus:
Base Features Provided: Tubing end seal connection Contact Action Stimulus: Increase
Base Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern:
Base Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line
Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement:
Base Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 2 pole, single throw, normally closed, momentary action
Base Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 2 pole, single throw, normally closed, momentary action Terminal Type:
Base Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 2 pole, single throw, normally closed, momentary action Terminal Type: Screw
Base Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 2 pole, single throw, normally closed, momentary action Terminal Type: Screw Contact Load Current Rating:
Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 2 pole, single throw, normally closed, momentary action Terminal Type: Screw Contact Load Current Rating: 35.0 amperes resistive load second voltage
Features Provided: Tubing end seal connection Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 2 pole, single throw, normally closed, momentary action Terminal Type: Screw Contact Load Current Rating: 35.0 amperes resistive load second voltage Contact Adjustability:

Shelf Life:

Contact Adjustment Type:
External actuation point knob
Contact Voltage Rating In Volts:
240.0 ac at sea level first voltage

N/a

NSN 5930-00-538-2973

Thermostatic Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0