

View Online at <https://aerobasegroup.com/nsn/5930-00-538-3406>

Overall Length:

5.312 inches

Overall Height:

4.656 inches

Overall Width:

1.906 inches

Body Height:

2.656 inches

Unthreaded Mounting Hole Diameter:

0.406 inches

Longest Horizontal Distance Between Mounting Centers:

4.500 inches

Longest Vertical Distance Between Mounting Centers:

1.812 inches

Pressure Switch Type:

Gage

Mounting Method:

Flush and unthreaded hole

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

4.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+250.00 actuation point pounds per square inch and +85.00/+225.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Stimulus Rating:

15.00 differential point pounds per square inch and 25.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

230.0 dc at sea level third voltage

Pressure Connector Type:

Flared, threaded external all connections

Special Features:

Shortest vertical distance between mtg centers 0.531 in.

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0