

View Online at <https://aerobasegroup.com/nsn/5930-00-538-3406>

**Overall Length:**

5.312 inches

**Overall Height:**

4.656 inches

**Overall Width:**

1.906 inches

**Body Height:**

2.656 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.500 inches

**Longest Vertical Distance Between Mounting Centers:**

1.812 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flush and unthreaded hole

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.4375 inches single pressure connection

**Mounting Facility Pattern:**

Obtuse triangle

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

4.6 amperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+100.00/+250.00 actuation point pounds per square inch and +85.00/+225.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point knob with scale and external actuation point knob with scale

**Contact Stimulus Rating:**

15.00 differential point pounds per square inch and 25.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

230.0 dc at sea level third voltage

**Pressure Connector Type:**

Flared, threaded external all connections

**Special Features:**

Shortest vertical distance between mtg centers 0.531 in.

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unc all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0