## NSN 5930-00-538-4730

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-538-4730

## **Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:** 

4.188 inches

**Body Diameter:** 

Between 0.618 inches and 0.625 inches

**Body Length:** 

3.562 inches

**Overall Diameter:** 

1.250 inches

**Unthreaded Mounting Hole Diameter:** 

0.221 inches

**Tempurature Sensing Element Type:** 

Expanding shell

**Mounting Facility Circle Radius:** 

0.625 inches

**Operating Tempurature Rating:** 

Between -100.0 degrees fahrenheit and 1000.0 degrees fahrenheit

**Mounting Method:** 

Flange and unthreaded hole

**Contact Action Stimulus:** 

Increase

**Mounting Facility Pattern:** 

Three position circular

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally closed, momentary action

**Terminal Type:** 

Tab w/screw

**Contact Load Current Rating:** 

5.0 amperes resistive load second voltage

**Contact Adjustability:** 

Actuation point adjustable, preset

**Contact Adjustment Range:** 

-100.00/+400.00 actuation point degrees fahrenheit

**Contact Adjustment Type:** 

External actuation point screw

**Contact Stimulus Rating:** 

48.00 actuation point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

240.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

## NSN 5930-00-538-4730

Thermostatic Switch - Page 2 of 2



Ctv/la	n Da	eian	ator:
OLYN	- 00	əiyii	atoi.

Cylindrical w/flange

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0