NSN 5930-00-538-4921

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-538-4921 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.625 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Overall Height:** 1.078 inches **Overall Width:** 0.281 inches **Body Length:** 1.203 inches **Body Width:** 0.281 inches **Body Height:** 0.859 inches **Case Material:** Metal **Unthreaded Mounting Hole Diameter:** 0.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.625 inches **Actuator Style:** Round **Actuator Diameter:** 0.094 inches **Actuator Height:** 0.219 inches **Maximum Voltage Rating In Volts:** 30.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action single switch unit **Switch Release Force:** 12.0 grams **Switch Actuating Force:**

27.0 grams

NSN 5930-00-538-4921

Sensitive Switch - Page 2 of 2



Actuator	Movement:
----------	-----------

Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes inductive ac

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0