# NSN 5930-00-538-4921

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-538-4921

## Body Style:

Hole mounted

#### Hazardous Locations/environmental Protection:

Dustproof

## **Overall Length:**

1.625 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

#### **Overall Height:**

1.078 inches

#### **Overall Width:**

0.281 inches

#### Body Length:

1.203 inches

## Body Width:

0.281 inches

## Body Height:

Body Holghi.

## 0.859 inches

Case Material:

Metal

#### **Unthreaded Mounting Hole Diameter:**

0.094 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.625 inches

#### Actuator Style:

Round

#### Actuator Diameter:

0.094 inches

#### **Actuator Height:**

0.219 inches

#### Maximum Voltage Rating In Volts:

30.0 ac

## Inclosure Type:

Fully enclosed

## Mounting Method:

Unthreaded hole

## Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

## Switch Release Force:

12.0 grams

## Switch Actuating Force:

27.0 grams

# NSN 5930-00-538-4921

Sensitive Switch - Page 2 of 2



#### **Actuator Movement:**

Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes inductive ac

## Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A053a0