NSN 5930-00-538-5328

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Watertight

Overall Height: 17.625 inches Overall Width: 6.312 inches Shaft Length:

2.406 inches single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-538-5328

Unthreaded Mounting Hole Diameter:
0.531 inches single mounting facility
Individual Section Quantity:
10
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9s5564l
Longest Horizontal Distance Between Mounting Centers:
7.875 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
4.125 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
2 each section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
120.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.379 inches single actuator
Terminal Type:
Tab w/screw

NSN 5930-00-538-5328

Rotary Switch - Page 2 of 2



Contact Switching Action	on:	Acti	hing	vitcl	S١	ntact	Con
--------------------------	-----	------	------	-------	----	-------	-----

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0