NSN 5930-00-538-5328

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Watertight

Overall Height: 17.625 inches Overall Width: 6.312 inches Shaft Length:

2.406 inches single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-538-5328

| Unthreaded Mounting Hole Diameter: |
|---|
| 0.531 inches single mounting facility |
| Individual Section Quantity: |
| 10 |
| Knob Manufacturer Code: |
| 80064 |
| Knob Manufacturer Part Number: |
| 9s5564l |
| Longest Horizontal Distance Between Mounting Centers: |
| 7.875 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 4.125 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 2 each section front |
| Throw Quantity: |
| 2 each section front |
| Mounting Method: |
| Bracket single mounting facility |
| Features Provided: |
| Actuator knob and metallic inclosure |
| Contact Voltage Rating In Volts: |
| 120.0 ac at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 2 single actuator |
| Shaft Type: |
| Rectangular/square, threaded hole single actuator |
| Square Shaft Size: |
| 0.379 inches single actuator |
| Terminal Type: |
| Tab w/screw |

NSN 5930-00-538-5328

Rotary Switch - Page 2 of 2



| Contact Switching Action | on: | Acti | hing | Switc | ontact S | C |
|--------------------------|-----|------|------|-------|----------|---|
|--------------------------|-----|------|------|-------|----------|---|

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0