## NSN 5930-00-538-5560

Pressure Switch - Page 1 of 2



- 1-0-0-0-1-0-1-0-1-0-1-0-1-0-1-0-1-0-1-
View Online at https://aerobasegroup.com/nsn/5930-00-538-5560
Thread Class:
3b single pressure connection
Inside Diameter:
0.438 inches single connection
Overall Length:
3.000 inches
Overall Height:
2.620 inches
Overall Width:
2.620 inches
Body Diameter:
2.370 inches
Body Length:
1.760 inches
Unthreaded Mounting Hole Diameter:
Between 0.219 inches and 0.233 inches
Longest Horizontal Distance Between Mounting Centers:
2.125 inches
Longest Vertical Distance Between Mounting Centers:
2.125 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.4375 inches single pressure connection

**Mounting Facility Pattern:** 

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

**Terminal Type:** 

Wire lead

**Contact Load Current Rating:** 

4.0 amperes resistive load single voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point not adjustable

## NSN 5930-00-538-5560

Pressure Switch - Page 2 of 2



Contact	<b>Stimulus</b>	Rating:
---------	-----------------	---------

35.00 actuation point pounds per square inch and 5.00 differential point pounds per square inch

## **Contact Voltage Rating In Volts:**

29.0 dc at sea level single voltage

## **Pressure Connector Type:**

Plain, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/mounting lugs

**Thread Series Designator:** 

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A048b0