

View Online at <https://aerobasegroup.com/nsn/5930-00-538-5675>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

1.875 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Overall Diameter:**

1.250 inches

**Nonturn Device Radius:**

0.531 inches at 12: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

4 1st section rear

**Throw Quantity:**

2 1st section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 1st section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load highest ac voltage rating at sea level

**Precious Material And Location:**

Rotor blades and spring clips silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0