NSN 5930-00-538-5853

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-538-5853

Dustproof
Overall Height:
2.500 inches
Overall Width:
2.375 inches
First Flat Length:
0.438 inches single actuator
Flat Height:
0.188 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.812 inches single actuator
Individual Section Quantity:
2
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-74000pc2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
3 each section front
Mounting Facility Circle Radius:
1.156 inches single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
120.0 dc at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:

Round, flatted, threaded hole single actuator

NSN 5930-00-538-5853Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Test Data Document:
81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single mounting facility
Specification Or Standard:
1sr2e2 type
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A052b0