

View Online at <https://aerobasegroup.com/nsn/5930-00-539-6596>

Hazardous Locations/environmental Protection:

Watertight

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.594 inches single actuator

Unthreaded Mounting Hole Diameter:

0.500 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

3.812 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 each section front

Throw Quantity:

4 each section front

Mounting Method:

Bracket single mounting facility

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

25.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0