## NSN 5930-00-539-6596

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-539-6596

Hazardous Locations/environmental Protection:
Watertight
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
0.594 inches single actuator
Unthreaded Mounting Hole Diameter:
0.500 inches single mounting facility
Individual Section Quantity:
2
Longest Horizontal Distance Between Mounting Centers:
3.812 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Pole Quantity:
1 each section front
Throw Quantity:
4 each section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Metallic inclosure
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
25.0 amperes resistive load ac at sea level
Shelf Life:
N/a
Unit Of Measure:

## NSN 5930-00-539-6596

Rotary Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A052b0

