NSN 5930-00-539-6596

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-539-6596

Hazardous Locations/environmental Protection: Watertight Shaft Diameter: 0.375 inches single actuator Shaft Length: 0.594 inches single actuator Unthreaded Mounting Hole Diameter: 0.500 inches single mounting facility Individual Section Quantity: 2 Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front Switch Actuator Positioning Increment:
Shaft Diameter: 0.375 inches single actuator Shaft Length: 0.594 inches single actuator Unthreaded Mounting Hole Diameter: 0.500 inches single mounting facility Individual Section Quantity: 2 Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
0.375 inches single actuator Shaft Length: 0.594 inches single actuator Unthreaded Mounting Hole Diameter: 0.500 inches single mounting facility Individual Section Quantity: 2 Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Shaft Length: 0.594 inches single actuator Unthreaded Mounting Hole Diameter: 0.500 inches single mounting facility Individual Section Quantity: 2 Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Unthreaded Mounting Hole Diameter: 0.500 inches single mounting facility Individual Section Quantity: 2 Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Unthreaded Mounting Hole Diameter: 0.500 inches single mounting facility Individual Section Quantity: 2 Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Individual Section Quantity: 2 Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Longest Horizontal Distance Between Mounting Centers: 3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
3.812 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Switch Contact Basic Design: Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Nonpile-up nonsymmetrical Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Pole Quantity: 1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
1 each section front Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Throw Quantity: 4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
4 each section front Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Mounting Method: Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Bracket single mounting facility Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Features Provided: Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Metallic inclosure Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
4 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Round single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Tab w/screw Contact Switching Action: Breaks before makes each section front
Contact Switching Action: Breaks before makes each section front
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
25.0 amperes resistive load ac at sea level
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-00-539-6596

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0