## NSN 5930-00-539-6600

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-539-6600 **Overall Length:** 3.687 inches **Overall Height:** 1.188 inches Overall Width: 1.531 inches **Body Length:** 2.000 inches **End Application:** Communications terminal, satellite an/gsc=39 9v)1, aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130), 485l tacs, teletype, model 28, aircraft, hercules c-130, aircraft, stratolifter c-135, aircraft, eagle f-15, support equipment, b-1 aircraft, satellite communications terminal, an/gsc-5 (v). **Mounting Method:** Clamp **Contact Action Stimulus: Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Criticality Code Justification:** Feat **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load first voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 2450.00 actuation point feet per minute and 2250.00 actuation point feet per minute and 2250.00 actuation point feet per minute and 2350.00 actuation point feet per minute and 1600.00 deactuation point feet per minute and 1250.00 deactuation point feet per minute and 1500.00 deactuation point feet per minute and 1550.00 deactuation point feet per minute and 850.00 differential point feet per minute **Contact Voltage Rating In Volts:** 250.0 ac at sea level first voltage **Special Features:** Weapon system essential Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas or liquid **Style Designator:** 

Domilitarization.

**Unit Of Measure:** 

Rectangular Shelf Life:

N/a

## NSN 5930-00-539-6600

Flow Switch - Page 2 of 2



Fiig:

A048b0