NSN 5930-00-539-6611

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-539-6611 **Thread Class:** 2b **Body Style: Bushing mounted Overall Length:** 1.375 inches **Overall Height:** 0.688 inches **Overall Width:** 0.688 inches **Body Diameter:** Between 0.552 inches and 0.572 inches **Bushing Length:** Between 0.298 inches and 0.328 inches **Body Length:** Between 0.888 inches and 0.920 inches **Case Material:** Metal **Actuator Style:** Round **Actuator Diameter:** Between 0.370 inches and 0.377 inches **Actuator Height:** Between 0.240 inches and 0.260 inches **Actuator Color:** Black single actuator **Illuminated Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **End Application:** Aircraft phanton f-4 **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi):

24

Thread Size: 0.625 inches

NSN 5930-00-539-6611

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action, with contact on arm single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread	Series	Des	ignator:
--------	--------	-----	----------

Unef

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0