## NSN 5930-00-539-6731

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-539-6731

| Center To Center Distance Between Mounting Facilities Parallel To Length:                |
|--|
| 1.000 inches   |
| Body Length:   |
| 1.938 inches   |
| Body Width:  |
| 1.688 inches   |
| Body Height:   |
| 0.953 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.140 inches   |
| Actuator Free Position Height:   |
| 1.125 inches   |
| Maximum Voltage Rating In Volts:   |
| 460.0 ac and 250.0 dc  |
| Nonpile-up Contact Arrangement:  |
| 1 pole, double throw, one position momentary single switch unit                          |
| Switch Release Force:  |
| 4.0 ounces   |
| Switch Actuating Force:  |
| 130.0 ounces   |
| Actuator Movement:   |
| Between 0.016 pretravel inches and 0.062 overtravel inches and 0.002 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 250.000 milliamperes resistive dc and 500.000 milliamperes resistive ac                  |
| Terminal Type And Quantity:  |
| 3 screw  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A053a0   |
|  |
|  |