

View Online at <https://aerobasegroup.com/nsn/5930-00-540-8306>

Body Style:

Bushing mounted

Body Diameter:

0.560 inches

Bushing Length:

0.750 inches

Body Length:

1.060 inches

Actuator Diameter:

0.380 inches

Actuator Height:

0.250 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.500 amperes inductive dc and 2.500 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 2.500 amperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Terminal Type And Quantity:

5 tab, solder lug

Specification Data:

81349-mil-s-22885/46 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0