

View Online at <https://aerobasegroup.com/nsn/5930-00-540-8311>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Watertight

Bushing Length:

Between 0.450 inches and 0.490 inches

Body Length:

1.340 inches

Body Width:

0.910 inches

Body Height:

1.120 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.245 inches

Actuator Height:

Between 1.110 inches and 1.210 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0