

View Online at <https://aerobasegroup.com/nsn/5930-00-543-0754>

Thread Length:

0.375 inches single mounting facility

Overall Length:

Between 2.714 inches and 2.786 inches

First Flat Length:

0.433 inches single actuator and 0.443 inches single actuator

Shaft Diameter:

0.246 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.844 inches single actuator and 0.906 inches single actuator

Overall Diameter:

Between 1.933 inches and 1.943 inches

Nonturn Device Radius:

0.526 inches at 10: 00 o'clock and 0.536 inches at 10: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 10: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Shaft Flat/slot Angular Location:

120.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, v flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0